

# Z-BOOX ZH

- ✓ Chassi **Rack 4U**
- ✓ Até **90 Baías** Hot-Swap
- ✓ **1Gb e 10Gb Base-T e SFP+**
- ✓ Fonte **redundante**



Z-BOOX.

## Até **200 streams** de vídeo

Pode chegar a **600TB** de espaço útil,  
e permitindo até 200 streams  
de vídeo **simultâneos**.

# Z-BOOX ZH

ZBOOX	ZH12	ZH24	ZH36	ZH60
HOT-SWAP SATA HARD DRIVES 3.5" 7200RPM	12	24	36	60
USABLE STORAGE CAPACITY	24 - 48 TB	55 - 200 TB	180 - 300 TB	160 - 500 TB
DATA PROTECTION	RAID 60 / RAID Z2			
PERFORMANCE	300 MB/s Random Access 40 XDCAM-HD 50	500 MB/s Random Access 66 XDCAM-HD 50		600 MB/s Random Access 80 XDCAM-HD 50
NETWORKING	Dual Gigabit Ethernet Base-T 10 Gigabit Ethernet (optional)	Dual 10 Gigabit Ethernet Base-T Dual 10 Gigabit Ethernet SFP+ fibre or copper cable		
NETWORK PROTOCOL COMPATIBILITY	AFP, SMB, NFS, FTP			
OPERATING SYSTEM	LINUX			
OPERATIONAL SYSTEM COMPATIBILITY	MacOS, Windows and Linux			
DIMENSIONS	Height: 89 mm (2U), Width: 440 mm, Depth: 652 mm	Height: 178 mm (4U), Width: 440 mm, Depth: 660 mm	Height: 178 mm (4U), Width: 440 mm, Depth: 767 mm	
WEIGHT	25Kg	60Kg	72Kg	
ELECTRICAL	Redundant 920W power supply Input 100-240V, 50-60Hz	Redundant 1200W high-efficiency power supply Input 100-240V, 50-60Hz		
OPERATING ENVIRONMENTAL	5°C ~ 35°C (41°F ~ 95°F); 8% ~ 90% (non-condensing)			